Canon

imageRUNNER ADVANCE DX **8905i/8995i/8986i**

imageRUNNER ADVANCE DX 8900 Series

Black-and-white High-volume Multifunction

Print up to 105 ppm (BW)

Scan up to 270/270 ipm (300 dpi) (BW/colour, duplex)

Print up to 13" × 19"

8,020-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience that can be tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder, and automatically print with pre-defined settings such as number of copies and finishing requirements.

SECURITY

- Advanced standard security feature set that's consistent across the entire imageRUNNER ADVANCE DX platform.
- Integrates with existing, third-party SIEM² systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at setup. Includes automatic recovery of boot process for self resiliency.
- McAfee Embedded Control³ utilizes whitelisting to help protect against malware and tampering of firmware and applications.
- Security settings can be controlled with a single touch via Canon's Recommended Security Settings. Configure security policy settings from a central location, and export to other supported devices.
- Control access to the device and specific features using a host of flexible authentication methods—PIN code, user name/password, or card access.⁴



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE DX models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT


- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR[®] certified

CONFIGURATION OPTIONS



* Staple Finisher-AC1 and Booklet Finisher-AC2 are not compatible with Document Insertion Unit-R1, Multi Function Professional Puncher-C1, and Paper Folding Unit-K1.

** Staple-free stapling, up to five pages of 17 lb. Bond.

Main Unit	
Type Monochrome L	aser Multifunctional
Core Function	
Standard:	Print, Copy, Scan, Send, Store
Optional: Processor	Fax
1.8 GHz Dual C	ore Processor
Control Panel	
Standard:	10.1" TFT LCD WSVGA colour Flat-panel
Optional:	10.4" TFT LCD SVGA colour Upright-panel
Memory 4.0 GB RAM	
Solid State Dr	ive
Standard:	256 GB
Maximum:	1 TB
Mirroring:	Optional
Interface Con Network:	nection 1000Base-T/100Base-TX/10Base-T
Optional: Others	Wireless LAN (IEEE 802.11 b/g/n)
Standard:	USB 2.0 (Host) x1, USB 3.0 (Host) x1, USB 2.0 (Device) x1
Optional:	Copy Control Interface
	ty (LTR, 20 lb. Bond)
Standard: Maximum:	4,360 Sheets 8,020 Sheets
	Capacity (LTR, 20 lb. Bond)
With Copy Tray:	
With External	5,000 Sheets (with Staple Finisher-AG1
Finishers:	or Booklet Finisher-AG1)
Finishing Cap With Options:	
with options.	Collate, Group, Offset, Staple, Saddle- Stitch, Hole Punch, Eco Staple, Staple
	On Demand, Document Insertion, Z-fold,
	Halffold, C-fold, Accordion-Z fold, Double
	Parallel-fold, Trimming
Supported Me Multi-purpose	Thin, Plain, Recycled, colour, Heavy, Tracing,
Tray:	Bond, Transparency, Labels, Pre-punched, Letterhead, Tab
Paper Decks:	Thin, Plain, Recycled, colour, Heavy, Bond,
_	Pre-punched, Letterhead
Paper Cassettes:	Thin, Plain, Recycled, colour, Heavy, Bond, Pre-punched, Letterhead, Tab ⁷
Supported Me	
Multi-purpose	13" x 19", 12" x 18", 11" x 17", Legal, Letter,
Tray:	Letter-R, Executive, Statement-R Custom
Den en De elver	Size/Free Size (4" x 5-7/8" to 13" x 19-1/4")
Paper Decks: Paper	Letter 13" x 19", 12" x 18", 11" x 17", Legal, Letter,
Cassettes:	Letter-R, Executive, Statement-R, Custom
	Size (5-1/2" x 7-1/8" to 13" x 19-1/4")
Supported Me	edia Weights
Paper Decks/ Cassettes:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m ²)
Multi-purpose	
Tray:	14 lb. Bond to 140 lb. Index (52 to 256 g/m
Duplexing:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m ²)
Print/Copy Sp	eed
8905i:	Up to 105 ppm (Letter)
	Up to 81 ppm (Letter-R) Up to 63 ppm (Legal)
	Up to 53 ppm (11" x 17")
8995i:	Up to 95 ppm (Letter)
	Up to 73 ppm (Letter-R)
	Up to 60 ppm (Legal) Up to 49 ppm (11" x 17")
8986i:	Up to 86 ppm (Letter)
	Up to 67 ppm (Letter-R)
	Up to 57 ppm (Legal) Up to 43 ppm (11" x 17")
Warm-up Tim	
	c : Approx. 60 Seconds ⁸
From Sleep	

From Sleep Mode: Approx. 60 Seconds^s **Ouick Startup** Mode. 4 Seconds or less¹⁰ Dimensions (W x D x H) 26-3/8" x 30-3/8" x 46-5/8" Standard: (670 mm x 770 mm x 1,185 mm) With Optional Upright 46-1/8" x 30-3/8" x 49-1/4" Touch-panel: (1,170 mm x 770 mm x 1,252 mm) Installation Space (W x D) Basic: 60-3/8" x 53-1/4" (1,533 x 1,353 mm)¹¹ Fully Configured: 199-1/2" x 55-1/2" (5.068 x 1.409 mm)¹² Weight Standard: Approx. 487.2 lb. (221 kg)13 With Optional Upright Touch-panel: Approx. 496.0 lb. (225 kg)13

Print Specifications

Print Resolution (dpi) 1200 x 1200 Standard Page Description Languages UFR II, PCL[®]6, Adobe[®] PS[®] 3

Supported File Types PDF, TIFF, JPEG, EPS,¹⁴ XPS

Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Universal Print by Microsoft[®], Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information. Fonts

93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional
Chinese), ¹⁵ Barcode fonts ¹⁶
136 Roman

Operating System¹⁷

PCL:

PS'

UFRII/PS:	Windows®10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, MAC OS X (10.13 or later)
PCL:	Windows [®] 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, MAC OS X (10.13 or later)
PS:	Windows®10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, MAC OS X (10.13 or later)
PPD:	Windows®10/11, MAC OS X (10.13 or later)

Copy Specifications

First-Copy-Out Time As Fast as 2.7 Seconds Copy Resolution (dpi) 600 x 600 Multiple Copies Up to 9,999 Copies Magnification 25%-400% (1% Increments) Preset Reduction/Enlargement 25%, 50%, 64%, 73%, 78% 100% (1:1), 121%, 129%, 200%, 400%

Scan Specifications

Туре

Single-pass Duplexing Automatic Document Feeder **Document Feeder Paper Capacity** Up to 200 Sheets (20 lb. Bond) **Document Feeder Supported Media Sizes** 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,

Custom Size [2-3/4" x 5-1/2" to 12" x 17" (70.0 mm x 139.7 mm to 304.8 mm x 431.8 mm)] Document Feeder Supported Media Weights
 Single-sided
 13 lb. Bond to 80 lb. Cover

 Scanning:
 (50 to 220 g/m²)

 Double-sided
 13 lb. Bond to 80 lb. Cover

 Scanning:
 (50 to 220 g/m²)

Platen Acceptable Originals Sheet, Book, 3-Dimensional Objects

Platen Max. Scanning Size

Up to 11-3/4" x 17" (297 mm x 431.8 mm) Pull Scan

Colour Network ScanGear2 for both Twain and WIA Supported OS: Windows®10/11/Server 2012/ Server 2012 R2/Server 2016/Server 2019/Server 2022

Scan Resolution (dpi)

Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/ IFAX), (Pull) 600 x 600 Scan for Copy: 600 x 600 Scan for Fax: 600 x 600

Scan to Mobile Devices and Cloud-based Services A range of solutions is available to provide scanning to mobile devices or and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning BW/colour: 135/135 (300 dpi), 135/80 (600 dpi) Double-sided Scanning BW/colour: 270/270 (300 dpi), 165/90 (600 dpi)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Communication Protocol

File:	FTP (TCP/IP), SMB 3.1.1 (TCP/IP), WebDAV
Email:	SMTP. POP3

File Format

TIFF, JPEG, PDF(Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS(Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications (Optional)

Maximum Number of Connection Lines

Modem Speed

 Super G3:
 33.6 Kbps

 G3:
 14.4 Kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement-R to 11" x 17

Fax Memory Up to 30,000 Pages (2,000 Jobs) Speed Dials Max. 200

Group Dials/Destinations Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup Yes

Store Specifications

Mail Box (Number Supported) 100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Up to 30,000 Pages (2,000 Jobs) Stored Advanced Box Communication SMB or WebDAV Protocol: Supported Windows (Windows 10/11) Client PC: Concurrent Connections (Max.): SMB: 64 WebDAV: 3 Advanced Box Available Disc Space Approx. 16 GB (Standard) Approx. 480 GB (Optional)

Security Specifications

Authentication and Access Control

User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Depertment ID and PIN Login, Function Level Login), uniFLOW Online Express¹⁸ (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control) Document Security

Print Security (Secure Print, Encripted Secure Print, Forced Hold Printing, uniFLOW Secure Print²¹), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/ Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark)

Network Security

TLS 1.3, IPSec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/ Wired LAN), Disabling Unused Functions (Enabling/ Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Box in the MFP, Scan and Send -Virus Concerns for E-mail Reception

Device Security

Protecting SSD Data (SSD Data Encryption (FIPS 140-3, pending validation), SSD Lock), Standard SSD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup³, Automatic Recovery, Runtime Intrusion Detection), Common Criteria Certification (HCD-PP)(pending confirmation) Device Management and Auditing

Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

Environmental Specifications

Operating Environment Temperature: 50 to 86 °F Humidity: 20 to 80 % RH (Relative Humidity) Power Requirements 110-127V, 60 Hz, 16A Power Consumption Åpprox. 2,032 W Maximum: Sleep Mode: Approx. 0.9 W or less19 Professional Imaging Product Production Energy²⁰ 8905i: .28 Wh/image 8995i .28 Wh/image 8986i .29 Wh/image Standards ENERGY STAR® Certified

Consumables

Toner GPR-37 Black Toner Toner Yield (Estimated @ 6% Coverage) 70,000 Pages

- ¹ Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.
- ² Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.
- ³ This feature is off by default and must be turned on by the
- user. Warm-up times are affected once turned on. ⁴ Requires additional option.
- ⁵ Some types of tracing paper cannot be used.
- ⁶ Tab Feeding Attachment-B1 is required.
- ⁷ Time from device power-on until copy ready (not print reservation).
- ⁸ Time from exiting Sleep mode to when printing is operational.
 ⁹ Time from device power-on to when the copy icon appears
- and is enabled to operate on the touch panel display.
- ¹⁰ With Multi-purpose Tray/upper-right cover open + Front cover open + Copy Tray.
- ¹¹ With POD Deck Lite-C1 + Document Insertion Unit-R1 +

Multi Function Professional Puncher-C1 + Paper Folding Unit-K1 + Booklet Finisher-AG1 + Booklet Trimmer-G1 + Main unit front cover open.

¹² Including the toner bottle.

¹³ EPS can be printed directly only from the Remote User Interface. ¹⁵ Requires the optional PCL International Font Set-A1.

- ¹⁴ Requires optional Barcode Printing Kit-D1
- ¹⁵ Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- ¹⁶ No charge for this solution; however, activation is required.
 ¹⁷ 0.9 W Sleep mode may not be possible in all circumstances
- due to certain settings. ¹⁸ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.
- ¹⁹ Requires uniFLOW Online/uniFLOW



AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks of canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. Trelix and the Trelix logo are trademarks of Musarubra US LLC and/or their affiliates in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21, or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for trypographical errors.

©2023 Canon Canada, Inc. All rights reserved.





To learn about Canon's many awards, visit canon.ca/awards.